

VYDAS

INTERNATIONAL MARKETING

Specialist Sensors & Instruments for Industry



PRESSURE METER MPC202

APPROPRIATION

The two-channel pressure meter MPC202 is appropriated to liquids, vapours and gases pressure measurement and to liquid level measurement. As a measurement element can be used PT series piezoresistive pressure sensor or PLH liquid level probe of PELTRON (4).

The wide assortment of sensors and level probes offered by the producer gives the possibility of the pressure and level measurement in the range correspondingly $-1...400$ bar and $0.5...100$ m H₂O. The MPC202 meter supplies the pressure sensor and converts the received measurement signal in the standard current or voltage output signal.

CHARACTERIZATION

- Industrial execution
- Simply in use
- Digital readout of measured values
- Aesthetic housing

CONSTRUCTION

All parts of the meter are placed inside the Al alloy housing consisting of two parts: the base and the cover. On the base of the housing is assembling an electronic circuit and digital indicator. In the cover is an indicator window having a contrast filter. Power, input and output cables comes out through glands. The device has holders for a clamping to a wall or board. The meter consist of:

- two amplifier systems
- the overvoltage protection system
- the digital indicator
- the power supply unit
- the channel switch
- the housing
- he range switch giving the possibility of 4 times changing of the measurement range using only one transducer (option).

The meter is available in different versions according to the ordering code.

PRINCIPLE OF OPERATION


The amplifier system has a current source for pressure sensor supply. The sensor output signal is converting to the standard voltage or current output signal.

The continual development of our products causes a necessity of changes introduction which can not be published in this document

TECHNICAL DATA

Power supply:	220V / 50Hz, 4VA or 24V DC
Input:	
Inputs quantity	2
Output:	
Outputs quantity	2
Output signal	0...20mA or 4...20mA , 0...5V or 0...10V
Load resistance (R)	≤500 Ω for current output, >2000Ω for voltage output
Range switch (option)	25%, 50%, 75% and 100% of max. measurement range
Digital indicator:	
Kind of display	13 mm height, 3 ½ digit red LED, option 10 mm height, 4 ½ digit red LED
Max. readout range	1999 for 3 ½ version, 19999 for 4 ½ digit version
Units	bar, mH ₂ O, mA, other
Overload indic.	is lighting only the first „1" digit for 3 ½ digit version display flashes for 4 ½ digit version
Polarity sign	minus
Indication error	≤ 0,3% ±1 digit for the 3 ½ digit ≤ 0,1% ±1 digit for the 4 ½ digit
Other parameters:	
Basic error	≤ 0,1% of measurement range
Operating temperature	0...+60°C; option -20°C...+80°C
Relative humidity	20... 90%
Housing protection	IP65
Weight	approx.. 1,5kG
2 wire system	only for 4...20mA output signal, 24V DC power supply, without of readout indicator; others - 3 wire system


DIMENSIONS:



The continual development of our products causes a necessity of changes introduction which can not be published in this document

ORDERING INFORMATION

Specify the model according to the ordering code:
Pressure meter



Ordering example:

MPC202-S-42-0-3-B

- MPC202 – two-channel pressure meter
- S – 220V/50Hz mains power supply
- 42 – 4...20mA output signal
- 0 – without change of range
- 3 – 3 ½digit digital indicator
- B – units - bar

Notes:

1. The standard version: MPC202-S-42-0-0.
2. The indicator can to show only the same units for both channels.
3. Measurement conditions: the power supply 24V – 0,5 V DC.
4. Error values are related to full range.
5. The meter ought to be ordered together with pressure transmitters or pressure level probes.
6. Using of the range switch the display readout is correct, if the digital indicator is calibrated in units of the output signal.



VYDAS INTERNATIONAL MARKETING
Swan House PBC Lynchborough Rd
Passfield Hampshire GU30 7SB UK

Tel: 44 (0)1428 751822 Fax: 44 (0)1428 751833
Email: info@vydas.co.uk Web: www.vydas.co.uk

PELLIRON® Ltd