

Moulded Case


TAIBB, TAS20B, TAS21, TAS23



TAIBB

Cable aperture 21mm dia
Secondary Terminals M4 screws
Weight 180g

Supplied with fixing feet, hinged terminal covers and DIN rail adaptor.




Primary current A	Burden		
	cl. 0-5 VA	cl. 1 VA	cl. 3 VA
40	-	-	1
50	-	1.25	1.5
60	-	1.25	2
70	-	1.5	2.5
75	-	1.5	2.5
80	-	1.5	2.5
100	2	2.5	3.5
120	2.5	3.5	4
125	2.5	3.5	4
150	3	4	5
160	3	4	5
200	4	5.5	6
250	5	6	7
300	6	7.5	8

5A secondary

TAS21

Cable aperture 17mm dia
Busbar window 20x5mm
Secondary Terminals M4 screws/fast-on connectors
Weight 200g

Supplied with fixing feet and busbar mounting bracket.



Primary current A	Burden		
	cl. 0-5 VA	cl. 1 VA	cl. 3 VA
50	-	-	1.5
60	-	-	1.5
80	-	-	2
100	-	1.5	2.5
120	-	2	3
150	-	2.5	4
200	2	4	6


1A or 5A secondary

Option: DIN rail adaptor
Terminal cover

TAS20B

Cable aperture 22mm dia
Busbar window 20x5mm
Secondary Terminals M4 screws/fast-on connectors
Weight 250g

Supplied with fixing feet, busbar mounting bracket and built-in 35mm DIN rail clip.



Primary current A	Burden		
	cl. 0-5 VA	cl. 1 VA	cl. 3 VA
50	-	-	2
60	-	-	2.5
80	-	-	3
100	-	2	4
120	-	3	5
150	2	4	6
200	3	6	8
250	5	8	10



1A or 5A secondary

Option: Terminal cover

TAS23

Cable aperture 23mm dia
Busbar window 30x10mm, 25x12mm, 20x11mm
Secondary Terminals M4 screws/fast-on connectors
Weight 250g

Supplied with fixing feet and busbar mounting bracket



Primary current A	Burden		
	cl. 0-5 VA	cl. 1 VA	cl. 3 VA
150	-	-	1.5
200	-	2	3
250	-	2	3
300	2	3	4
400	3	4	5
500	4	5	6
600	5	6	8

1A or 5A secondary

Option: DIN rail adaptor
Terminal cover